


## **METER BOXES**

Rade Koncar-TEP

## ■ BOXES FOR HALF-INDIRECT METERING

Туре	Order numbers	Dimensions (mm) Width-High-Depth w h d	No. of cables		maksim.	
			Incoming 4x150mm2	Outgoing 4x150mm2	Current (A)	Mounting
MO-NM - Z-300 polyester	701951677	529x823x255	1	1	300	on wa <b>l</b> l
MO-NM - F-600 metal	701180667	740x1250x330	2	2	600	on fundament
MO-NM - Z-600 metal	701181667	740x1250x330	2	2	600	on wa <b>l</b> l
MO-NM - St-600 metal	701182667	740x1250x330	2	2	600	on pi <b>ll</b> ar
MO-NM - F-1000 metal	701952667	1070x1250x330	3(240)	3(240)	1000	on fundament
MO-NM - F-1500 metal	701953667	1070x1250x330	4(240)	4(240)	1500	on fundament

Boxes for half-indirect metering are used in LV networks, mostly for outdoor mounting on fundament, pillar and on wall. They are made according to the standard EN 60439 and other norms that are pertaining to these types of boxes. Material: polyester or galvanized metal sheets that are electrostatic painted with epoxy powder, with colour that is resistant to the external atmospheric influence. Standard shade in our use is RAL 7035 (other colours are available on request).





## ■ BOXES FOR SUMMARY, HALF-INDIRECT AND INDIRECT METERING

Туре	Order number	Dimensions(mm) Width-High-Depth w h d	vo <b>l</b> tage circuits		Material	Mounting
MO-NM - Summary	701183667	500x600x230	400V~	5A	metal	on wa <b>ll</b>
MO-NM - Summary	701184667	530x640x245	400V~	5A	polyester	on wa <b>ll</b>
MO-NM - Indirect	701185667	530x640x245	100V~	5A	polyester	on wa <b>ll</b>

Boxes for summary, half-indirect, and indirect metering are used in LV networks, for outdoor and indoor mounting on wall. They are made according to the standard EN 60439 and other norms that are pertaining to these types of boxes. Material: Polyester, and galvanized metal sheets that are electrostatic painted with epoxy powder, with colour that is resistant to the external atmospheric influence. Standard shade in our use is RAL 7035 (other colours are available on request). Degree of protection is IP55 for metal boxes and IP44 for polyester boxes, according to EN 60529. Meter boxes are supplied with complete equipment for fastening.





